

Encartonadora Sleeve de Cartão - MP 70



Descrição:

A **MP-70** é uma **Encartonadora de Sleeve** totalmente automática com uma capacidade de 50 sleeves por minuto. Com uma revista que pode suportar até 1.000 caixas, o MP-70 permite a rápida mudança de tamanho da caixa (dentro de 10 a 15 minutos). Fácil e simples de configurar, operar e manter. O MP-70 pode ser fornecido com diferentes tipos de alimentadores, incluindo: pick & place, side pusher ou qualquer outro empurrador lateral rotativo.

Produção	Até 50 sleeves por minuto
Peso	850 Kg
Potência	380 V, 3 fases, 50/60 Hz, 4Kw
Medida mín. do sleeve	(C) 60mm x (L) 60mm x (A) 30mm
Medida máx. do sleeve	(C) 280mm x (L) 200mm x (A) 200mm
Consumo de ar	200 L/min a 6 bar

Exemplos de Produtos





SLEEVE WRAPAROUND CARTONER Model MP-70

The **MP-70** is a fully automatic, intermittent sleeve wraparound cartoner that handles up to 50 sleeves per minute. With a magazine that can handle up to 1,000 cartons, the MP-70 is fully AC motor and servo system controlled and enables fast changing of carton size (within 10 - 15 minutes).

Easy and simple to set up, operate and maintain, the MP-70 achieves a nice pack and full area for printing, with the seal area remaining invisible.

The MP-70 can be supplied with different type of feeders, including: pick & place, side pusher or any other rotary side pusher.



WE DESIGN FOR HUMAN SAFETY - THAT IS OUR MAIN GOAL

Technical Data

- AC motors.
- In feed conveyor.
- Automatic product feeding with different type of Operating Systems.
- Full diagnostic fault alarm.
- Generator vacuum source.
- HMI 7" touch screen.
- Adjustable Carton magazine.
- Hot melt glue system.
- Stainless steel construction.
- CE mark.

Options

- Right Left version available.
- Fully servo system.
- Partial wrap around.

Applications

Bottles, jars, cans, plastic containers, trays, etc.
Any configuration can be considered:

- 2,3,4 side pack. • 1 or 2 rows. • 1-2 layers.

Specifications

Production speed: Up to 50 Wraps Per Minute.

Net weight: 850 KG.

ELECTRICAL REQUIREMENTS:

Input Power:

380 V, 3 Phase

50/60 Hz, 4 KW.

other possibilities also available.

WRAP SIZE RANGE:


Minimum:

(L) 60mm (2.3") (W) x 60mm (2.3") (H) x 30mm (1.18")

Maximum:

(L) 280mm (11") (W) x 200mm (8") (H) x 200mm (8")

Special application upon request.



AIR REQUIREMENTS:

Operating pressure: 88psi (6 atm)

Line pressure: 103 psi (7 atm)

Air consumption: 200 L/min at 6 bar

Hot melt air pressure 20-59 psi (1.4 - 4 atm)

